

ACCESSORIES

CLEANING UNIT



Automatic cleaning of machine parts after printing

Gentle removal of 1 and 2 component ink

ORIGINAL

TAMPOPRINT

60 YEARS
1956-2016

Pad Printing Machines
ALFALAS® Laser Systems
Automations



Stainless steel cleaning tanks with removable stainless steel basket



Storage space for cleaning agent integrated in the cleaner (Cleaning agent not included in the delivery)

Technical data:

Cleaner		
Item no.		14 23 25
Housing material		Galvanized sheet steel
Material of cleaning tank		Stainless steel (AISI 430 2B)
Operating pressure max.	bar	10
Air consumption/h	Nm ³	16
Cleaning area (width x depth x height)	approx. mm	410 x 500 x 150
Storage weight grid cleaning area	max. kg	10
Height (incl. exhaust pipe)	mm	1,230 (1,730)
Width	mm	530
Depth	mm	710
Weight	approx. kg	58

Scope of delivery

- Stainless steel basket
- Stainless steel holders + aluminium support rods for cliché cylinders
- Exhaust pipe
- Ground cable
- Drip pan
- Documentation

Accessories

- Detergent RM Item No. 12 94 01
Content 30 litre
- Cleaning tissues Item No. 14 21 64
(Box / 200 sheets)
- Cleaning tissues Item No. 23 86 85
(Roll / 750 sheets)
- Protective goggles Item No. 44 00 07
- Gloves, acid-resistant Item No. 14 12 07

Technical specification:

Pneumatic cleaning device for washing of ink/doctoring cups and clichés for pad printing.

The cleaning area made of stainless steel can be reached via a flap in the top panel. Here during operating spray nozzles spread the cleaning agent on the dirty parts. The cleaner is kept in a separate housing area which is to be opened from the front side. Existing hoses suck the cleaning agent directly from the container. The cleaning process and its duration are controlled by a "timer".

By means of an integrated security system the cleaning process is interrupted by premature opening of the cover flap. The washing solvent vapours which are produced while washing are sucked off automatically. For removal, we recommend an on-site suction unit.

The cleaner conforms to the legislative proposals 94/9/ EC (ATEX Directive) and 2006/42/ EC (Machinery Directive).

Prerequisites:

- On site existing air pressure connection and suction unit
- Very well ventilated device location
- Smooth and even surface

Contact:

Accessories and spare parts
Fax: +49 7150 928-0
mailto: salesparts@tampoprint.de



TAMPOPRINT® AG

Lingwiesenstraße 1
70825 Korntal-Münchingen, GERMANY
☎ +49 7150 928-0
Fax: +49 7150 928-400
E-Mail: info@tampoprint.de
Ventes et Affaires Françaises
☎ +49 7150 928-144
Fax: +49 7150 928-432
E-Mail: ventes@tampoprint.de
http: www.tampoprint.de

TAMPOPRINT® INTERNATIONAL CORP.

1400 26th Street, Vero Beach, FL 32960, USA
☎ +1 772 778-8896, 800 810-8896
Fax: +1 772 778-8289
E-Mail: sales@tampoprint.com
http: www.tampoprint.com

TAMPOPRINT® IBERIA S.A.U.

Polígono Industrial Martorelles,
C/ Sant Martí, s/n (entre Gorgs y Mogent)
08107 Martorelles (Barcelona), SPAIN
☎ +34 93 2327161
Fax: +34 93 2471500
E-Mail: tampoprint@tampoprint.es
http: www.tampoprint.es



The reproduction of trademarks and brands used in this brochure, even if not explicitly expressed, does not justify the assumption that such names or symbols may be considered as free as defined by the Trademark Act and may therefore freely be used. The rights are the property of the respective owner.

TAMPOPRINT products are permanently updated to keep pace with the latest technological developments. For this reason, figures and descriptions are non-binding. Our machines are manufactured based on the currently valid European Machinery Directives as well as the European product standards EN 1010 - 1 and EN 1010 - 2.

Subject to alterations! ©Copyright